



## JS-35E

### Specification

- Card type: EM
- Working voltage: DC 12-24V
- Operating current:  $\leq 100\text{mA}$
- Operating temperature:  $-40^{\circ}\text{C}\sim 60^{\circ}\text{C}$
- Operating humidity:  $0\%\sim 95\%$
- Idle current:  $\leq 35\text{mA}$
- Lock output load:  $\leq 1\text{A}$
- Short-circuit protect:  $\leq 100\mu\text{s}$
- Reading range: 2-6cm

### Feature:

- 2000 card/code users
- Wg26-37 Input/Output
- Can set admin add/delete card
- Access ways: Card, Code, Mobile phone APP Tuya function
- Support remote unlock
- Manage users with mobile phone App
- Set temporary code, Check visitor records

## JS-35E Features (via Tuya -SmartLife App)

- Devices can be seamlessly added to the Tuya (SmartLife) mobile app.
- User enrollment and deletion can be initiated directly through the app.
- OTP (One-Time Password) can be generated via the mobile app for secure access.
- Access logs can be monitored in real-time on the app.
- Remote unlocking is possible via mobile app.
- Doorbell notifications are received instantly through the app.

Disclaimer : Brief specifications are mentioned here. Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.