

APP BASED ACCESS CONTROL

“Leave keys behind. Manage access with a single app”

-  Face
-  Fingerprint
-  Mobile App
-  Card
-  Password



Mobile based access control device

JS-35E

- Card type: EM
- Working voltage: DC 12-24V
- Operating current: $\leq 100\text{mA}$
- Operating temperature: $-40^{\circ}\text{C}\sim 60^{\circ}\text{C}$
- Operating humidity: $0\%\sim 95\%$
- Idle current: $\leq 35\text{mA}$
- Lock output load: $\leq 1\text{A}$
- Short-circuit protect: $\leq 100\mu\text{s}$
- Reading range: 2-6cm



JS-36E

Touch Fingerprint Access Control with LCD Screen

- Card type: Proximity
- Working voltage: DC 12-24V
- Operating current: $\leq 100\text{mA}$
- Operating temperature: $-40^{\circ}\text{C}\sim 60^{\circ}\text{C}$
- Operating humidity: $0\%\sim 95\%$
- IP65 rated
- Idle current: $\leq 35\text{mA}$
- Lock output load: $\leq 1\text{A}$
- Short-circuit protect: $\leq 100\mu\text{s}$
- Reading range: 2-6cm



JS-37E

Touch fingerprint Access Control with LCD Screen & Voice broadcast function

- Metal case design, touch keypad
- Semiconductor fingerprint sensor
- support 2000 card/code users, and 200 fingerprints
- Wg26 Input/output
- Access ways: Fingerprint, Card, Code, Mobile phone APP
- 3 working modes: Relay toggle mode, Standalone access control mode/ Pure reader mode
- With data backup function
- Can set admin add/delete card
- Adjustable volume, multiple language choices
- Outdoor IP66



JS-38E

Keypad Access Control

- Card type: Proximity
- Static electricity: $\leq 30\text{mA}$
- Working voltage: $\text{DC}12\text{V}\pm 10\%$
- Ambient temperature: $-45^{\circ}\text{C} \sim 60^{\circ}\text{C}$
- Reading Range: 3-6cm
- Electric lock output: $\leq 1\text{A}$
- Humidity: 10% to 90% RH
- Short-circuit Protect: $\leq 100\mu\text{S}$
- Door Opening Time: 0-99s(Adjustable)
- Dimensions: 115*75*20mm
- Indoor
- With Tuya wifi



JS-39E

3D Facial Recognition Access Control

- Card type: Proximity
- Static electricity: $\leq 30\text{mA}$
- Working voltage: $\text{DC}12\text{V}$ (Customizable 24V)
- Ambient temperature: $-45^{\circ} \sim 60^{\circ}$
- Humidity: 10% to 90% RH
- Card Reading Range: 2-5cm
- Facial Recognition Distance: 1m
- Electric lock output: $\leq 1\text{A}$
- Short-circuit Protect Time: $\leq 100\mu\text{S}$
- Door Opening Time: 0-99s(Adjustable)



MA-46E

- User Capacity: Hardware User: 10000 | APP User: 50
- Common Card/PIN User: 9988
- Common Fingerprint User: 500
- Visitor User: 10
- Panic User: 2





APP BASED ACCESS CONTROL

Tuya - SmartLife App

- Devices can be seamlessly added to the Tuya (SmartLife) mobile app.
- User enrollment and deletion can be initiated directly through the app.
- OTP (One-Time Password) can be generated via the mobile app for secure access.
- Access logs can be monitored in real-time on the app.
- Remote unlocking is possible via mobile app.
- Doorbell notifications are received instantly through the app.

