


JS-36E

Touch Fingerprint Access Control with LCD Screen



Specification

- Card type: Proximity
- Working voltage: DC 12-24V
- Operating current: $\leq 100\text{mA}$
- Operating temperature: $-40^{\circ}\text{C} \sim 60^{\circ}\text{C}$
- Operating humidity: $0\% \sim 95\%$
- IP65 rated
- Idle current: $\leq 35\text{mA}$
- Lock output load: $\leq 1\text{A}$
- Short -circuit protect: $\leq 100\mu\text{s}$
- Reading range: 2-6cm

Feature:

- with Voice broadcast function
- Semiconductor fingerprint sensor
- support 10000 card/code users ,and 200 fingerprints
- Wg26 Input/Output
- Access ways: Fingerprint, Card, Code, Mobile phone APP
- 3 Working modes: Relay toggle mode, Standalone access control mode/ Pure reader mode
- With data backup function
- Can set admin add/delete card
- Adjustable volume, multiple language choices
- Support remote unlock
- Set temporary code
- Check visitor records
- Manage users by mobile phone App

JS-36E Features (via Tuya -SmartLife App)

- Devices can be seamlessly added to the Tuya (SmartLife) mobile app.
- User enrollment and deletion can be initiated directly through the app.
- OTP (One-Time Password) can be generated via the mobile app for secure access.
- Access logs can be monitored in real-time on the app.
- Remote unlocking is possible via mobile app.
- Doorbell notifications are received instantly through the app.

Disclaimer : Brief specifications are mentioned here. Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.