

AIFACE SUN+POE



Product Feature:

- Display: 4.3" @ TFT Color Touch LED Screen (480*800)
- Camera: Binocular Camera @ 2MP WDR
- Operation System: Linux
- Authentication method: Fingerprint / Face / Card / Password (Virtual Keypad)
- User Capacity: 10,000
- Fingerprint Template Capacity: 10,000
- Face Template Capacity: 10,000
- Card Capacity: 10,000
- Transaction Capacity: 100,000
- Optional Card Type: Mifare, HID
- Max. User Password Length: 8 Digits
- Facial Recognition Speed: <0.35s
- Fingerprint Recognition Speed: <0.5s
- Touchless Biometric Recognition Distance: 30cm to 200cm @ Face
- Facial Recognition FAR: $\leq 0.01\%$
- Fingerprint FAR: $\leq 0.0001\%$
- Facial Recognition FRR: $\leq 0.02\%$
- Fingerprint FRR: $\leq 0.01\%$
- Communication: TCP/IP, Wi-Fi(Optional), Wiegand (Input & Output), RS485, USB,
- Optional Functions: Wi-Fi, 4G, Backup Battery
- Power Supply: DC 12V 3A PoE: IEEE 802.3af Backup Battery
- Access Control Interface: Electro Magnetic Lock/ Electric Lock, Door Sensor, Exit Button
- Operating Temperature: 0°C to 45°C
- Operating Humidity: 20% to 80% RH (Non-condensing)
- Dimensions: 193.00 mm*100.00 mm*32.40 mm (L*W*H)
- Supported Software: eTimetracklite Software

Disclaimer : Brief specifications are mentioned here. Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.