



EML600-8-FGD-Bracket

Technical Specifications

- Description: UL-style (or top-and-bottom) bracket set for frameless glass doors.
- Suitable glass thickness: 8–16 mm
- Required door gap: more than 5 mm [Clearance: A minimum gap of 5 mm is strictly required between the door and the frame (or between double door panels)]
- Material thickness: 2 mm
- Magnetic lock mounting hole spacing: 10 mm [Hole Pitch: The center-to-center distance between the mounting screw holes is exactly 10 mm]

Left Bracket: Upper Glass Header Clamp

- Total Length: 190 mm
- Base Width: 53 mm
- Total Height: 46 mm
- U-Channel Outer Width: 28 mm
- U-Channel Inner Opening: 16 mm (Fits 8–16 mm glass with padding)

Right Bracket: Armature Plate / Lower Door Clamp

- Total Length: 250 mm
- Armature Face Length: 197 mm
- Base Profile Width: 32 mm
- Total Bracket Height: 29 mm
- U-Channel Outer Width: 25 mm
- U-Channel Inner Opening: 16 mm (Fits 8–16 mm glass with padding)

Disclaimer : Brief specifications are mentioned here. Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.